

Features

- ◆ Universal Input Range 90~265V_{AC}
- ◆ Efficiency up to 91.5%
- ◆ Full Brick Size
- ◆ Class I
- ◆ Approval Meets IEC/EN/UL 62368-1
- ◆ Operating Altitude 5000m
- ◆ Remote On/Off
- ◆ Over Temperature Protection
- ◆ Over Voltage Protection
- ◆ Continuous Short Circuit Protection
- ◆ Baseplate Cooling



MODEL NUMBER	OUTPUT VOLTAGE	OUTPUT CURRENT	RIPPLE & NOISE NOTE1 & 2	VOLTAGE ACCURACY NOTE3	LINE REGULATION NOTE4	LOAD REGULATION NOTE5	%EFF. (Typ.) NOTE6
CFAF700S12	12V _{DC}	58.4A	120mV	±1.0%	±0.5%	±0.5%	87.5%
CFAF700S24	24V _{DC}	29.2A	240mV	±1.0%	±0.5%	±0.5%	90%
CFAF700S28	28V _{DC}	25.0A	280mV	±1.0%	±0.5%	±0.5%	90.5%
CFAF700S48	48V _{DC}	14.6A	480mV	±1.0%	±0.5%	±0.5%	91%
CFAF700S56	56V _{DC}	12.5A	560mV	±1.0%	±0.5%	±0.5%	91.5%

Note:

- External components are required. please refer to the application note.
- Add a 0.1uF ceramic capacitor and a 10uF E.L. capacitor to output for ripple & noise measuring @20MHz BW.
- Voltage accuracy is set at 60% load.
- Line regulation is measured from 100V_{AC} to 265V_{AC} with full load.
- Load regulation is measured from 60%±40% rated load.
- Typical efficiency at 230V_{AC} and full load at 25°C.
- When the aluminum case of brick reaches temperature 100°C. the unit will be OTP. the unit need sufficient convection and heat sink.

PART NUMBER

Series	Number of Outputs	Nominal Output Voltage
CFAF700	S	XX
CFAF700	S:Single	12V _{DC} 24V _{DC} 28V _{DC} 48V _{DC} 56V _{DC}

Part Number Example:

CFAF700S12:700W,Single 12V_{DC} Output

TECHNICAL SPECIFICATIONS

(All specifications are typical at nominal input, full load at 25°C unless otherwise noted.)

ABSOLUTE MAXIMUM RATINGS

PARAMETER	NOTES and CONDITIONS	Device	Min.	Typ.	Max.	Units
Input Voltage		All	90		265	V _{AC}
Operating Case Temperature	At the center of base plate	All	-40		100	°C
Storage Temperature		All	-55		105	°C
Operating Altitude		All			5000	m

INPUT CHARACTERISTICS

PARAMETER	NOTES and CONDITIONS	Device	Min.	Typ.	Max.	Units
Operating Voltage Range		All	100		240	V _{AC}
Input Frequency Range		All	47		63	Hz
Maximum Input Current	100% Load, V _{in} =100V _{AC}	All			9	A
Leakage Current	Only CFAF700S Brick	All			0.01	mA
Inrush Current	V _{in} =240V _{AC} , Cold Start at 25°C (External inrush resister 10Ω)	All			35	A
Under Voltage Protection		All	63	70	77	V _{AC}
Power Factor	230V _{AC} /50Hz @ Full load	All		0.97		

OUTPUT CHARACTERISTICS

PARAMETER	NOTES and CONDITIONS	Device	Min.	Typ.	Max.	Units
Output Voltage Set Point	V _{in} =115V _{AC} and 230V _{AC} , I _o =60% I _{o max} , T _c =25°C	CFAF700S12	11.88	12	12.12	V _{DC}
		CFAF700S24	23.76	24	24.24	
		CFAF700S28	27.72	28	28.28	
		CFAF700S48	47.52	48	48.48	
		CFAF700S56	55.44	56	56.56	
Operating Output Current Range	V _{in} =115V _{AC} and 230V _{AC} , T _c =25°C	CFAF700S12	0		58.4	A
		CFAF700S24	0		29.2	
		CFAF700S28	0		25.0	
		CFAF700S48	0		14.6	
		CFAF700S56	0		12.5	
Holdup Time	V _{in} =115V _{AC} (Refer to the application note)	All		16		mS
Output Voltage Regulation						
Load Regulation	20% Load to 100% Load	All			±0.5	%
Line Regulation	V _{in} =High Line to low line	All			±0.5	%
Output Voltage Trim Range	P _o max rated power, I _o ≤I _{o max}	CFAF700S56	-5		+1.8	%
		Others	-5		+5	
Over Current Protection	Hiccup mode, auto recovery	All	105		195	%
Over Voltage Protection	Latch off (recycle AC input to restart)	CFAF700S12		14.8	16.8	V _{DC}
		CFAF700S24		30.3	33.6	
		CFAF700S28		34.4	39.2	
		CFAF700S48		55.9	57.6	
		CFAF700S56		58.0	59.9	
Output Ripple and Noise	1. Add a 0.1uF ceramic capacitor and a 10uF aluminum electrolytic capacitor to output. 2. Oscilloscope is 20MHz band width. 3. Ambient temperature=25°C. 4. The output capacitor is necessary, such as load capacitance in the table below.	CFAF700S12		80	120	mV
		CFAF700S24		160	240	
		CFAF700S28		180	280	
		CFAF700S48		260	480	
		CFAF700S56		260	560	

PARAMETER	NOTES and CONDITIONS	Device	Min.	Typ.	Max.	Units
Load Capacitance	1. Ambient temperature=25℃ 2. Input voltage is 115V _{AC} and 230V _{AC} 3. Output is max. load	CFAF700S12	11700		58340	uF
		CFAF700S24	8000		29170	
		CFAF700S28	8000		25000	
		CFAF700S48	2820		14590	
		CFAF700S56	2820		12500	

EFFICIENCY

PARAMETER	NOTES and CONDITIONS	Device	Min.	Typ.	Max.	Units
Efficiency	1. Output is rated load 2. Ambient temperature=25℃ @ input voltage is 230V _{AC}	CFAF700S12		87.5		%
		CFAF700S24		90		
		CFAF700S28		90.5		
		CFAF700S48		91		
		CFAF700S56		91.5		

ISOLATION CHARACTERISTICS

PARAMETER	NOTES and CONDITIONS	Device	Min.	Typ.	Max.	Units
Input to Output	1 minute (without dielectric breakdown)	All			3000	V _{AC}
Input to Earth (Ground)	1 minute (without dielectric breakdown)	All			2000	V _{AC}
Output to Earth (Ground)	1 minute (without dielectric breakdown)	All			500	V _{AC}
Isolation Resistance	Input to Output	All	100			MΩ

FEATURE CHARACTERISTICS

PARAMETER	NOTES and CONDITIONS	Device	Min.	Typ.	Max.	Units
Switching Frequency		All		220		kHz
Over Temperature Shutdown	Temperature at the center part of base plate, auto recovery	All		110		℃
Over Temperature Recovery				105		


GENERAL SPECIFICATIONS

PARAMETER	NOTES and CONDITIONS	Device	Min.	Typ.	Max.	Units
MTBF	I _o =100%, T _a =25°C per MIL-HDBK-217F	All	250			k hours
Humidity	Non-condensing	All	93			% RH
Shock	Meets MIL-STD-810F Table 516.5,Table 516.5-I 10ms, each axis 3 times(±X、±Y、±Z axis)	All	75			g
Vibration	Meets MIL-STD-810F Table 514.5C-VIII,15~2000Hz, X、Y、Z axis, 1hr(each axis),. total 3 hrs.	All	4			g
Weight		All	210			grams
Dimensions		All	4.6x2.4x0.5 Inches (116.8x61.0x12.7mm)			
Case Material	Plastic DAP UL 94V-0					
Base Plate Material	Aluminum Baseplate					
Potting Material	UL 94V-0					
Safety	Class I, IEC/EN/UL 62368-1					
EMC Emission	EN55032					Class A
Conducted Disturbance	EN55032					Class A
Radiated Disturbance	EN55032					Class A
Harmonic Current Emissions	EN61000-3-2:2014					
Voltage Fluctuations & Flicker	EN61000-3-3:2013					
EMC Immunity	EN55035					
Electrostatic Discharge (ESD)	IEC 61000-4-2:2008, Air Discharge: ±8kV Contact Discharge: ±4kV					Criterion A
Radio-Frequency, Continuous Radiated Disturbance	IEC 61000-4-3:2020					Criterion A
Electrical Fast Transient (EFT)	IEC61000-4-4:2012, ±1kV, ±2kV					Criterion A

GENERAL SPECIFICATIONS





Surge	IEC61000-4-5:2014+A1:2017 L-N: $\pm 0.5\text{kV}$, $\pm 1\text{kV}$, $\pm 2\text{kV}$, L-E(ground): $\pm 0.5\text{kV}$, $\pm 1\text{kV}$, $\pm 2\text{kV}$, $\pm 4\text{kV}$	Criterion A
Conducted Disturbances, Induced by RF Fields	IEC 61000-4-6:2013+COR1:2015	Criterion A
Power Frequency Magnetic Field	IEC 61000-4-8:2009	Criterion A
Voltage Dips	IEC 61000-4-11:2004+A1:2017, Dip: 30% Reduction, Dip >95% Reduction	Criterion A
Voltage Interruptions	IEC 61000-4-11:2004+A1:2017, >95% Reduction	Criterion B


CHARACTERISTIC CURVE








Simplified Application Circuit

Power Derating Curve






Performance Data



MECHANICAL SPECIFICATION



CHEWINS Beijing Science & Technology Co., Ltd.

Address: No. 25, Torch South Street, Zhuozhou Development Zone, Hebei Province, People's Republic of China
Tel: 86-10-68817997 Mobile phone: 15600309099 E-mail: sales@chewins.net www.chewins.net